

TECHNICKÁ SPECIFIKACE

název série	šířka (L) mm	výška (H) mm	rozteč		hloubka		výkon při tep. spádu			váha kg	objem dm ³	koeficient n	doporučený výkon el.tyče W
			připojení		od zdi vč. radiátoru (G) mm	od zdi k přívodu (g) mm	55/45	75/65	90/70				
			klasické (hD) mm	středové (h) mm			20°C	20°C	20°C				
PIKO	430	629	400	50	83-103	68-88	132	248	311	3,80	1,60	1,2333	300
		729					150	283	355	4,30	1,80	1,2382	300
		979					195	370	464	5,60	2,40	1,2505	400
		1129					222	419	526	6,40	2,80	1,2454	400
		1329					258	485	608	7,50	3,20	1,2386	400
	530	729	500	50	83-103	68-88	171	322	404	4,80	1,99	1,2424	300
		979					223	421	528	6,30	2,64	1,2435	400
		1129					255	481	603	7,20	3,00	1,2412	400
		1329					298	562	704	8,50	3,60	1,2380	600
		1529					345	649	813	9,70	4,10	1,2340	600
		1679					381	714	894	10,60	4,50	1,2310	900
	630	629	600	50	83-103	68-88	166	315	396	4,80	1,90	1,2507	300
		729					190	360	452	5,40	2,20	1,2466	400
		979					251	471	591	7,00	2,89	1,2366	400
		1129					289	543	681	8,10	3,34	1,2370	600
		1329					339	638	800	9,40	3,90	1,2375	600
		1529					393	738	925	10,80	4,50	1,2363	900
		1679					433	814	1019	11,80	5,00	1,2354	900

